

8KVA

Hybrid Solar Inverter

IVGM Series Low-voltage | Split Phase

Features

- Configurable parameters and working mode by LCD touch screen.
- Supporting WiFi monitoring and Fsolar smart cloud monitoring system.
- Battery charge and discharge current up to 120A~190A.
- Prevent grid overload with built-in limit function while seamlessly switching between battery and grid supply within 10ms for uninterrupted power.
- IP65 protection level.
- Optimize energy use with Time-of-Use, Sell-First, and Zero Export options to maximize savings and efficiency.
- 4-channel PV, 2-channel MPPT, 1.5 times over configuration capacity.
- Programmable generator port, support smart load and micro inverter access.
- Support parallel operation with single-phase, and three-phase.
- Max. 6 units in parallel



IVGM8KLP2G1



Model	IVGM8KLP2G1
Battery Input Data	
Battery Voltage Range	40V~60V
Max. Charging and Discharging Current	190A/190A
Max. Charging and Discharging Power	8000W
Battery Type	Li-Ion /Lead-acid
DC Input Data(PV side)	
Max. Recommended PV Power	12000W
Max. PV Voltage	500V
Start Voltage	100V
PV Voltage Range	90V-500V
MPPT Voltage Range	120V-425V
MPPT Voltage Range for Full Load	230V-425V
Nominal Voltage	380V
Pv Input Current	26A+26A
Max. Shorted Current	44A+44A
Number of MPP Trackers / Strings Per MPP Tracker	2/2
Grid Data	
Nominal Input Voltage	120/240Va.c (Split Phase), 208Va.c (2/3 Phase)
Nominal Grid Frequency	50/60Hz
Max. AC Output Power	8800W
AC Output Rated Current	33.3A
Max. Output Current	36.7A
Max. Continuous AC Passthrough	50A
AC Output Data(Back Up)	
Rated Output Power	8000W
Max. Output Current	40A
Rated AC Output Voltage	120/240Va.c (Split Phase), 208Va.c (2/3 Phase)
Rated AC Output Frequency	50/60Hz
Protection	
Output Over Current Protection	Integrated
Output Over Power Protection	Integrated
Output Short-Circuit Protection	Integrated
Anti-islanding Protection	Integrated
GFCI Protection	Integrated
Arc Fault Circuit Interrupter(AFCI)	Integrated
Insulation Resistor Detection	Integrated
General Data	
Operating Temperature Range	-25°C~60°C, >45°C Derating
Protection Degree	IP65
Cooling Concept	Smart Cooling
Communication	RS232 / RS485
BMS Communication	CAN / RS485
Monitor Module	WiFi / GPRS
Display	LCD+LED
Installation Style	Wall-mounted
Warranty	10 Years
Grid Regulation(In progress)	VDE 4105、CEI 0-21、G99、NRS 097-2-1、EN 50549-1、EN 50549-10、NC RFG(Poland)、EN 50549-1/-10+Netherlands、PPDS、NTS & UNE217001 & UNE217002、UL1741
Safety Regulation	IEC 62109-1/-2
EMC	IEC/EN 61000-6-1/2/3/4、EN/IEC 61000-3-11/12
Net Weight(KG)	33.5KG
Gross Weight(KG)	40.5KG
Product Dimension(MM)	430*654*243MM
Package Dimension(MM)	787*547*358MM

*Refer to Felicitysolar's Warranty Policy for applicable conditions.





SISTEMA DE BATERIA LiFePO4

Modelo LPBF 48100 - 48200 - H



Parámetros del producto

Models	LPBF48100-H	LPBF48200-H
Usable Capacity	5KWH	10KWH
Nominal Voltage	51.2	51.2
Voltage Range	48-57.6	48-57.6
MAX.Charge& Discharge Current	100A@30S	120A@30S
Recommend Charge & Discharge Current	≤50A	≤80A
MAX.Output Power	5000W	6000W
Recommend Output Power	2500W	4000W
DOD	≥95%	
Modules Connection	1-6in parallel	
Communication	CAN&RS485	
Ingress Protection	IP21	
Cycle Life	≥6000@25°C ,80%DOD	
Working Temperature Range	Discharge:-20°C to +65°C, Charge:+0°C to +55°C	
Net Weight(KG)	63KG	75KG
Gross Weight(KG)	76KG	88KG
Product Dimension(mm)	575*430*258mm	685*475*213mm
Package Dimension(mm)	670*525*415mm	780*570*375mm

Perspectiva de producto

